



Majorpack reziPLY17 cost-effective solution - epoxy-phenolic polymer based protective coating, designed to protect tubing in milder corrosive environments with excessive asphaltene-resin-paraffin deposits (ARPD).

Key features	reziPLY17
Polymeric color	White beige glossy
Coating type	Epoxy phenolic
Polymeric thickness	5.6 - 14 mils (140 - 350 microns)
Coating roughness	5 microns
Anticorrosion properties	Protection against mild H ₂ S Protection from high sweet corrosion (CO ₂) Abrasive wear resistance
Acid/alkaline treatments	Acid treatments: 10% HCl, t=50°C, max. duration: 24 hours Alkaline treatments: 10% NaOH, t=50°C, max. duration: 24 hours
Polymeric temperature limit	230°F (110°C)
Short-time polymeric temperature limit	392°F (200°C)
Polymeric layer adhesion, not less than	12 MPa

TYPES OF PROTECTION – ARPD

KEY BENEFITS OF MAJORPACK

- ARPD control efficiency
- Corrosion control efficiency
- Cost efficiency
- Ample production capacities
- Reducing carbon footprint
- Ultra-low surface roughness

3 - 18

times is the operation cost reduction depending on the degree of complication

85,000

tons of products are manufactured yearly

18,200

wells in operation globally with majorpack® protective coatings

Get in touch with your local Majorpack representative now and see how we can lower your costs today!

Majorpack Inc.

Energy Corridor, 11111 Katy Freeway,
Suite 910, Houston, TX 77079 USA
Phone: +1 713 973 5761, +1 713 973 57 62
Fax: +1 713 973 5777
Email: info@majorpack.com
web: majorpack.com

We are an emerging leader in industry standards of anti-corrosion coating technology for OCTG. Years of extensive research and product development have demonstrated that multifaceted systems are necessary for complete corrosion protection of downhole tubing.