



Majorpack reziPLY99 cost-effective solution -  
 - epoxy-phenolic polymer based protective coating, designed to protect tubing in milder corrosive environments with excessive asphaltene-resin-paraffin deposits (ARPD).

Key features	reziPLY99
Polymeric color	Brown glossy
Coating type	Epoxy phenolic
Polymeric thickness	5.6 - 14 mils (140 - 350 microns)
Coating roughness	3 microns
Anticorrosion properties	More than 4 l/µm
Acid/alkaline treatments	Protection against mild H <sub>2</sub> S Protection from sweet corrosion (CO <sub>2</sub> ) Protection from ARPD Thread protection Abrasive wear resistance
Polymeric temperature limit	Acid treatments: 10% HCl, t=50°C, max. duration: 24 hours Alkaline treatments: 10% NaOH, t=50°, max. duration: 24 hours
Short-time polymeric temperature limit	302°F (150°C)
Polymeric layer adhesion, not less than	392°F (200°C)

**TYPES OF PROTECTION**  
 – ARPD  
 – CORROSION

**KEY BENEFITS OF MAJORPACK**

- ARPD control efficiency
- Corrosion control efficiency
- Cost efficiency
- Ample production capacities
- Reducing carbon footprint
- Ultra-low surface roughness

**3 - 18**  
 times is the operation cost reduction depending on the degree of complication

**85,000**  
 tons of products are manufactured yearly

**18,200**  
 wells in operation globally with majorpack® protective coatings

**Get in touch with your local Majorpack representative now and see how we can lower your costs today!**

**Majorpack Inc.**  
 Energy Corridor, 11111 Katy Freeway,  
 Suite 910, Houston, TX 77079 USA  
 Phone: +1 713 973 5761, +1 713 973 57 62  
 Fax: +1 713 973 5777  
 Email: info@majorpack.com  
 web: majorpack.com

We are an emerging leader in industry standards of anti-corrosion coating technology for OCTG. Years of extensive research and product development have demonstrated that multifaceted systems are necessary for complete corrosion protection of downhole tubing.